

Openwell Submersible Pumps:-

“Teraflo” brand make highly efficient durable and best Quality openwell submersible pump.



SALIENT FEATURES

1. Design for wide voltage range.
2. Manufactured using a much sophisticated control process to ensure reliability & Long life of the pump.
3. Design for underwater Application.
4. Light weight& easy to install.
5. Impeller made from glass filled engineer polymer for better life.
6. Full Stainless steel stator tube as well as stainless steel shaft.
7. Supply with control panel.

MATERIAL OF CONSTRUCTION

Stator Tube	: Stainless Steel / Cast Iron FG 200 Grade.
Thrust Bearing	: Carbon
Impeller	: Glass Filled engineering polymer/Cast iron FG 200
Pump Volute	: Cast Iron FG 200 Grade.

APPLICATION

1. Domestic water supply-Apartment, Building & Hotel
2. Fountains.
3. Canals& Rivers
4. Irrigation from openwell where water level fluctuate.

TECHNICAL SPECIFICATION

Head Range	: 6 to 68 Meter.
Discharge Range	: 50 to 2344 LPM
Motor Rating	: 0.5HP to 5HP (Single Phase) 0.5HP to 20 HP (Three Phase)
Voltage Range	: 140V to 250V (1 Phase) 200V to 440V (3 Phase)

